

All Rights Reserved

Materials and specifications are subject to change without notice.
Featured machines in photos may include additional equipment.
See your XCMG dealer for available options.

"XCMG", "WWW.XCMG.COM", "XCMG For Your Success",
as well as the corporate and product identity used herein,
are trademarks of XCMG and may not be used without permission.



XCMG Road Rollers



XCMG Regional Departments:

Europe	(+86-516) 87739238 87739271 87739228	Central Asia	(+86-516) 87739218 87739236 87739538
West Asia & North Africa	(+86-516) 87739252 87739202 87739223	North America	(+86-516) 87739285 87739551 87739715
Asia-Pacific	(+86-516) 87739289 87739500 87739529	Latin America	(+86-516) 87739237 87739714 87739710
Africa	(+86-516) 87735009 87739222 87739283		

XUZHOU CONSTRUCTION MACHINERY GROUP IMP. & EXP. CO., LTD

Fax: (+86-516) 87739230

Add: No.1, Tuolanshan Road, Xuzhou Economic Developing Zone, Jiangsu, China 221004

E-mail: yangjj@xcmg.com

www.xcmg.com

Double Drum Vibratory Rollers



XD102

Double Drum Vibratory Rollers



Main Specifications

Description		Parameter	Unit
Mass Distribution	Operating weight	10000	kg
	Axle load,front	5000	kg
	Axle load,rear	5000	kg
Compacting Performance	Static linear load	280/280	N/cm
	Nominal amplitude	0.40/0.80	mm
	Vibration frequency	48/45	Hz
	Centrifugal force	60/120	kN
	Dimension of vibrating drum	1150×1750	mm
Mobility	Speed	0 ~ 9.5	km/h
	Theoretical gradeability	30	%
	Minimum turning radius (inside/outside)	4065/5815	mm
	Oscillating angle	±8	°
	Steering angle	±38	°
Engine	Model	DEUTZ BF4M2012-10T3R	
	Type	Linear four-cylinder water-cooling type	
	Rated power	74.9	kW
	Rated speed	2300	r/min



CASE

